

# ENVIROFLEX® PVC

7 oz/yd<sup>2</sup> | 237 g/m<sup>2</sup>

**Applications:**

Outdoor Advertising  
Banners  
POP  
Trade Shows

**Widths Available**

Up to 196 in | 5 m

**Added Benefits:**

Recyclable  
RF and Hot Air Weldable  
Lightweight  
FR Certified

**Solvent, UV, and Latex Printable**



.....

**Enviroflex® PVC Frontlit** is an environmentally conscious, lightweight, vinyl billboard and banner substrate used in both indoor and outdoor applications. This frontlit solution boasts a 40 percent lower carbon footprint and weight than standard flexible vinyl—yet its durability and printability are comparable to heavier premium vinyl substrates.

*For further information,  
please contact Cooley  
Commercial Graphics:*

Cooley Group  
50 Esten Avenue  
Pawtucket, RI 02860  
Tel: 401.724.9000  
Email: [cginfo@cooleygroup.com](mailto:cginfo@cooleygroup.com)  
[cooleygroup.com](http://cooleygroup.com)

## ENVIROFLEX® PVC

7 oz/yd<sup>2</sup> | 237 g/m<sup>2</sup>

## TECHNICAL DATA

**Roll Widths** (*custom widths available*)

Standard	Metric
126 in	3.2 m
150 in	3.8 m
174 in	4.4 m
196 in	5.0 m

**Description**

Coating Type	PVC
--------------	-----

Material Properties	ASTM Test Methods	Standard	Metric
Total Weight (nominal)		7 oz/yd <sup>2</sup>	237 g/m <sup>2</sup>
Tensile Strength, 1" Strip	D751-B	60 x 45 lbs	267 x 200 N
Tear Strength, Butterfly	D1004 (mod)	30 x 30 lbs	133 x 133 N
Hydrostatic Resistance	D751-B	200 psi	1.4 MPa
Ball Puncture	D751	130 lbs	578 N
Low Temp Bend	D2136	-30°F	-34°C
High Temp, Cont / Interm.	1204	180 / 200°F	82 / 93°C
Shrinkage	D1204	< 3%	< 3%
Fungus Resistant	G21	Yes	
Weldable		Dielectric (RF) or Thermal	
Flame Certifications	NFPA 701, CSFM, ASTM E84 (Class A), UBC 26-7 (Class CC1)		

**Applications**

Backlit	Banner	Billboard	Blockout	Bldg Wrap	Displays	Truckside
	●	●	●		●	

**Ink Compatibility** (*all inks must be tested for compatibility*)

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct	Eradicable	Latex
●	●	●	●				●

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.

For further information, please contact Cooley Commercial Graphics:  
401.724.9000 or [cginfo@cooleygroup.com](mailto:cginfo@cooleygroup.com)