COOLFLEX®

13 oz/yd² | 440 g/m²

Applications:

Outdoor Advertising Banners POP Trade Shows

Widths Available Up to 196 in | 5 m

Available in weights ranging from 7 oz/yd² | 237 g/m² to 16 oz/yd² | 542 g/m²

Added Benefits:

Recyclable RF and Hot Air Weldable Lightweight FR Certified

Solvent, Eco Solvent, and UV Printable



Coolflex® Banner is a premium vinyl billboard and banner substrate designed for indoor and outdoor applications. This lightweight, reinforced frontlit solution is digitally printable, designed for use with Solvent, Eco-Solvent, and UV printers; and it maintains its durability in addition to being recyclable.

For further information, please contact Cooley Commercial Graphics:

Cooley Group 50 Esten Avenue Pawtucket, RI 02860 Tel: 401.724.9000 Email: cginfo@cooleygroup.com

cooleygroup.com

13 oz/yd² | 440 g/m²

TECHNICAL DATA

Roll Widths			
Standard	Metric		
39 in	1.0 m		
54 in	1.4 m		
63 in	1.6 m		
98 in	2.5 m		
126 in	3.2 m		
137 in	3.5 m		
150 in	3.8 m		
174 in	4.4 m		
196 in	5.0 m		

Available in weights ranging from 7 oz/yd 2 | 237 g/m 2 to 16 oz/yd 2 | 542 g/m 2

Description					
Coating Type	PVC				
Scrim Type	Polyester 1000 x 1000 denier				

Material Properties	ASTM Test Methods	Standard	Metric	
Total Weight (+/- 10%)		13 oz/yd²	440 g/m²	
Tensile Strength, 1" Strip	D751-B	125 x 100 lbs	556 x 445 N	
Tear Strength, Trapezoidal	D4533	15 x 15 lbs	67 x 67 N	
Hydrostatic Resistance	D751-B	285 psi	2.0 MPa	
Ball Puncture	D751	300 lbs	1,334 N	
Low Temp Bend	D2136	-20°F	-29°C	
Shrinkage	D1204	< 2%	< 2%	
Weldable		Dielectric (RF) or Thermal		
Flame Certifications	NFPA 701			

Applications						
Backlit	Banner	Billboard	Blockout	Bldg Wrap	Displays	Truckside
	•	•		•	•	

Ink Compa	Ink Compatibility (all inks must be tested for compatibility)					
Solvent	Eco Solvent	UV	Screen Printing	Dye Direct	Eradicable	Latex
•	•	•	•			

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.

For further information, please contact Cooley Commercial Graphics: 401.724.9000 or cginfo@cooleygroup.com