

COOLMESH® MAX LITE

8 oz/yd² | 271 g/m²

Applications:

Indoor/Outdoor
Advertising

Building/Stadium/
Mural Wrap

Banner

Widths Available

Up to 196 in | 5 m

Added Benefits:

70/30 Flow-Through Ratio

Bright White Face

Lightweight

High Strength

Solvent, Eco-Solvent, and UV Printable



COOLMESH® Max Lite is a lightweight, high-strength building wrap and banner solution designed with a unique surface quality, providing more ink coverage and maximizing airflow (70/30 flow-through ratio). This mesh product solution is printable on both sides with UV ink and is suitable for large-format advertising, supporting both indoor and outdoor applications.

*For further information,
please contact Cooley
Commercial Graphics:*

Cooley Group

50 Esten Avenue

Pawtucket, RI 02860

Tel: 401.724.9000

Email: cginfo@cooleygroup.com

cooleygroup.com

8 oz/yd² | 271 g/m²

TECHNICAL DATA

Roll Widths

Standard	Metric
63 in	1.6 m
126 in	3.2 m
196 in	5 m

Description

Coating Type	PVC
Scrim Type	Polyester 1000 x 1000 denier

Material Properties	ASTM Test Methods	Standard	Metric
Total Weight (nominal)		8 oz/yd ²	271 g/m ²
Tensile Strength, 1" Strip	D751-B	155 x 140 lbs	689 x 623 N
Tear Strength, Trapezoidal	D4533	40 x 30 lbs	178 x 133 N
Air Flow (nominal)	D737	420 cfm/ft ²	2132 l/m ² /sec
Light Transmittance	CIE 172:2006 (mod)	35%	
Fungus Resistant	G21	Yes	
Weldable		Dielectric (RF) or Thermal	
Flame Certifications	NFPA 701		

Applications

Backlit	Banner	Billboard	Blockout	Bldg Wrap	Displays	Truckside
	●			●		

Ink Compatibility *(all inks must be tested for compatibility)*

Solvent	Eco Solvent	UV	Latex	Dye Transfer	Dye Direct	Eradicable
●	●	●	●			

CoolMesh® Max Lite is manufactured for use with inkjet printers including, but not exclusive to, Vutek™, HP/Scitex, and Durst series equipment.

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.

For further information, please contact Cooley Commercial Graphics:
401.724.9000 or cginfo@cooleygroup.com