# ENVIROFLEX® PE

5.9 oz/yd<sup>2</sup> | 200 g/m<sup>2</sup>

## **Applications:**

Indoor / Outdoor Billboards POP Backlit Displays

Widths Available
Up to 196 in | 5 m

#### **Added Benefits:**

**PVC Free** 

Recyclable

Lightweight

Strong

Translucent

**REACH Compliant** 

**UV Printable** 



**EnviroFlex® PE Backlit** is a lightweight, highly durable, recyclable substrate designed for backlit applications. This solution is produced using polyethylene—the world's most recycled plastic—offering excellent translucency for delivering vibrant colors in LED displays. The revolutionary substrate boasts a significantly lower carbon footprint and weight than standard flexible vinyl products, making it an ideal alternative to heavier premium vinyl substrates.

For further information, please contact Cooley Commercial Graphics:

Cooley Group
50 Esten Avenue
Pawtucket, RI 02860
Tel: +1 401.724.9000
Email: cginfo@cooleygroup.com
cooleygroup.com

## 5.9 oz/yd<sup>2</sup> | 200 g/m<sup>2</sup>

### **TECHNICAL DATA**

Roll Widths (custom widths available)				
Standard	Metric			
196 in	5 m			

Description				
Coating Type	PE (white / white)			
Scrim Type	Woven PE slit tape			

<b>Material Properties</b>	<b>ASTM Test Methods</b>	Standard	Metric	
Total Weight (nominal)	D751	5.9 oz/yd²	200 g/m²	
Tensile Strength, Grab	D5034	190 x 150 lbs	845 x 667 N	
Tensile Elongation, Grab	D5034	11%	11%	
Tear Strength, Tongue	D751-B	30 x 30 lbs	133 x 133 N	
Screwdriver Puncture	D751	30 lbs	133 N	
Low Temp Bend	D2136	-30°F	-34°C	
High Temp Shrinkage (212°F/100°C)	D1204	≤ 2%	≤ 2%	
Fungus Resistant	G21	Yes		
Weldable		Thermal	Thermal	

Applicatio	Applications							
Backlit	Banner	Billboard	Blockout	Bldg Wrap	Displays	Truckside		
		•						

Ink Com	Ink Compatibility (all inks must be tested for compatibility)						
Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct	Eradicable	Latex
		•					

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.

For further information, please contact Cooley Commercial Graphics: +1 401.724.9000 or cginfo@cooleygroup.com