



Americas • Asia • Europe • Middle East • Africa

TECHNICAL DATA SHEET

SoffTICK® 189-10

Mattress ticking

COATED FABRIC SPECIFICATIONS*

Total thickness (nominal)	17 mils
Total weight	10 oz/yd ²
Coating type	Flexible Vinyl
Coating distribution	50% back / 50% face
Sealing properties	<input checked="" type="checkbox"/> Dielectric <input type="checkbox"/> Thermal

* A variety of standard widths and colors are available. Please contact Cooley Customer Service at solutions@cooleygroup.com for more details.

MATERIAL PROPERTIES

PROPERTY	MINIMUM	TYPICAL	TEST METHOD
Grab Tensile (Warp)	90 lb/in	109 lb/in	ASTM D751
Grab Tensile (Fill)	93 lb/in	103 lb/in	ASTM D751
Trapezoid Tear (Warp)	22 lb	33 lb	ASTM D751
Trapezoid Tear (Fill)	22 lb	26 lb	ASTM D751
Adhesion (Warp)	7 lb/in	12 lb/in	ASTM D751
Adhesion (Fill)	14 lb/in	25 lb/in	ASTM D751
Flame Retardancy	Pass		Cal TB 117 - 2013
	Pass		NFPA 701 M2 flat
Antimicrobial	100% contact inhibition		AATCC Method 147
	100% surface inhibition		AATCC Method 30
Surface Resistivity	10 ¹⁰ Ohms (antistatic)		NFPA 99
Composition	83 % vinyl, 17 % polyester		ASTM D751

Comments:

Questions? Email: solutions@cooleygroup.com

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.