

VinaGYM® PR-19 TC  
Athletic gym curtains

TECHNICAL DATA

COATED FABRIC SPECIFICATIONS\*

Revision Date: 18 Mar 2025  
Expiry Date: 18 Mar 2030

Total Thickness (nominal)	23 mils
Total Weight	20 oz/yd <sup>2</sup>
Coating Type	Flexible Vinyl
Coating Distribution	50% back, 50% face
Sealing Properties	Dielectric   Thermal

\* A variety of standard widths and colors are available.

PROPERTY	MINIMUM	TYPICAL	TEST METHOD
Grab Tensile (Warp)	375 lb	425 lb	ASTM D751
Grab Tensile (Fill)	375 lb	430 lb	ASTM D751
Trapezoid Tear (Warp)	30 lb	45 lb	ASTM D751
Trapezoid Tear (Fill)	30 lb	45 lb	ASTM D751
Adhesion (Warp)	12 lb/in	16 lb/in	ASTM D751
Adhesion (Fill)	12 lb/in	16 lb/in	ASTM D751
Flame Retardancy	Pass	NFPA 701 M2 flat	
	Pass	CAN/ULC S109 large scale flat & folded	
	Pass	Cal State Fire Marshall	
	Class 1 or A	ASTM E84	

Comments:

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.