

Vina GARD® V-Clear2 | 13 oz  
Clear Cover Fabric

TECHNICAL DATA

COATED FABRIC SPECIFICATIONS\*

Revision Date: 26 Oct 2022  
Expiry Date: 2 Sept 2027

Total Thickness (nominal)	18 mils
Total Weight	12.6 oz/yd <sup>2</sup>
Coating Type	Flexible Vinyl
Coating Distribution	50% back, 50% face
Sealing Properties	Dielectric   Thermal

\* A variety of standard widths and colors are available.

PROPERTY	MINIMUM	TYPICAL	TEST METHOD
Grab Tensile (Warp)	80 lb/in	100 lb/in	ASTM D751
Grab Tensile (Fill)	100 lb/in	115 lb/in	ASTM D751
Trapezoid Tear (Warp)	25 lb	35 lb	ASTM D751
Trapezoid Tear (Fill)	35 lb	40 lb	ASTM D751
Adhesion (Warp)	10 lb/in	15 lb/in	ASTM D751
Adhesion (Fill)	10 lb/in	15 lb/in	ASTM D751
Flame Resistance	Pass		FMVSS, Method 302
Composition	94% vinyl, 6% polyester		ASTM D751

Comments: This is a preliminary specification based on limited data. Final production values may vary.

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.