

20 oz/yd² | 22 mils

TECHNICAL DATA

COATED FABRIC SPECIFICATIONS*

Revision Date: 3 May 2025
Expiry Date: 3 May 2030

Total Weight	20 oz/yd ²
Coating Type	PVC
Coating Distribution	Double Sided
Sealing Properties	Dielectric Thermal

* A variety of standard widths and colors are available.

PROPERTY		MINIMUM	TYPICAL	TEST METHOD
Tensile Strength, 1" Strip	Warp	140 lbs	155 lbs	ASTM D751
	Fill	130 lbs	145 lbs	ASTM D751
Tear Strength, Trapezoidal	Warp	30 lbs	40 lbs	ASTM D751
	Fill	20 lbs	30 lbs	ASTM D751
RF Seam Adhesion Strength		8 lbs/in	11 lbs/in	ASTM D751
Shrinkage (200°F)		<1.5%	1.0%	ASTM D1204
Light Transmission		30%		ASTM D1494
Low Temperature Bend		-30°F		ASTM D2136
High Temp, Cont/Interim		180/200°F		ASTM D1204
Mildew/ Fungus Resistance		No Growth		ASTM G21
Flame Resistance		Pass		NFPA 401 (small scale) NFPA (large scale) CSFM certified

The information contained herein or that is supplied by us, or on our behalf, is based upon data obtained through our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data, the results obtained from the use thereof, or that any such use will not infringe upon any patent. This information is furnished upon the condition that the person receiving it shall evaluate its suitability for the specific application.